

EXHIBIT A

US005794354A

United States Patent [19]

Gilder

[11] Patent Number: **5,794,354**
 [45] Date of Patent: **Aug. 18, 1998**

[54] **RAZORS**[75] Inventor: **Bernard Gilder, Berkshire, England**[73] Assignee: **The Gillette Company, Boston, Mass.**[21] Appl. No.: **643,117**[22] Filed: **Apr. 30, 1996****Related U.S. Application Data**

[62] Division of Ser. No. 244,039, May 20, 1994, Pat. No. 5,533,263.

[30] **Foreign Application Priority Data**

Nov. 27, 1991 [GB] United Kingdom 9125261
 Nov. 3, 1992 [GB] United Kingdom 9222984

[51] Int. Cl.⁶ **B26B 21/52**[52] U.S. Cl. **30/530; 30/50; 30/527**[58] Field of Search 30/47, 50, 527,
30/530, 532, 533[56] **References Cited**

(List continued on next page.)

U.S. PATENT DOCUMENTS


939,935 11/1909 Wilcox 30/50
 1,104,857 7/1914 Windham .
 1,226,322 5/1917 Engstrom .
 1,234,834 7/1917 Warren 30/47
 1,373,874 4/1921 Engstrom .
 1,396,645 11/1921 Madden 30/47
 1,479,690 1/1924 Angst .
 2,125,135 7/1938 Trippe .
 2,386,536 10/1945 Bensele 30/47
 3,593,416 7/1971 Edson 30/50
 3,938,247 2/1976 Carbonell et al. 30/47
 3,950,849 4/1976 Perry 30/47
 3,975,820 8/1976 Torrance 30/47
 4,026,016 5/1977 Nissen 30/47
 4,063,354 12/1977 Oldroyd et al. 30/47
 4,083,104 4/1978 Nissen et al. 30/47
 4,094,063 6/1978 Trotta 30/47
 4,198,746 4/1980 Trotta 30/89
 4,200,976 5/1980 Gooding 30/47
 4,227,302 10/1980 Torrance 30/47
 4,253,235 3/1981 Jacobson 30/47

FOREIGN PATENT DOCUMENTS

0020816-A1 1/1981 European Pat. Off. .
 0357821-A1 3/1990 European Pat. Off. .
 0357821-B1 3/1990 European Pat. Off. .
 56-1191 1/1981 Japan .
 7603885 10/1977 Netherlands .
 1460732 1/1977 United Kingdom .
 714122 8/1994 United Kingdom .
 92/17322 10/1992 WIPO .

Primary Examiner—Hwei-Sui Payer*Attorney, Agent, or Firm*—Fish & Richardson P.C.[57] **ABSTRACT**

A safety razor including a blade unit with a guard, three blades, a cap with a lubricating strip, a front pivot and a substantially unobstructed rinsing space under the blades between the guard and cap.

13 Claims, 3 Drawing Sheets

5,794,354

Page 2

U.S. PATENT DOCUMENTS

5,224,267	7/1993	Simms et al.	30/50	5,347,717	9/1994	Ts'ai	30/89
5,249,361	10/1993	Apprille, Jr. et al.	30/77	5,416,974	5/1995	Wain	30/50
5,253,237	10/1993	Jacobson	30/89	5,426,851	6/1995	Gilder et al.	30/50
5,333,383	8/1994	Ferraro	30/87	5,533,263	7/1996	Gilder	30/530
				5,546,660	8/1996	Burout et al.	30/50





Fig. 1.





U.S. Patent

Aug. 18, 1998

Sheet 3 of 3

5,794,354



5,794,354

1

RAZORS

This is a divisional of application Ser. No. 08/244,039, filed May 20, 1994 now U.S. Pat. No. 5,533,263.

BACKGROUND OF THE INVENTION

This invention relates to razors, and is particularly concerned with a safety razor of the kind comprising a handle and a blade unit mounted on the handle with the capability to Divot during shaving to adjust itself to the contours of the surface being shaved, there being spring means acting between the handle and blade unit to urge the blade unit to a "rest" position.

In known razors of this kind the pivot axis, as seen in a direction perpendicular to a plane containing the guard surface and the edge of the blade adjacent to the guard, is located between the guard and the cap of the blade unit, i.e. generally behind the blade or blades, and the blade unit is arranged to pivot in both directions from its rest position. With such arrangements the handle tends to impede flow of water through the blade unit for rinsing away soap and shaving debris.

SUMMARY OF THE INVENTION

In accordance with the present invention there is provided a safety razor comprising a blade unit including a guard and at least one blade, and a handle mounting the blade unit for pivotal movement in one direction only from a rest position, characterised in that the pivot axis underlies the guard surface as seen in a direction normal to a plane containing the guard surface and the edge of the adjacent blade.

With the pivot axis located to underly the guard surface, the force of the blades against the skin during shaving will be mainly influenced by the spring means which opposes pivotal displacement of the blade unit from the rest position and applies a restoring force to return the blade unit to the rest position when it has been deflected from that position. As a consequence if the user wishes to apply more force to the guard, for example to stretch the skin, this can be done without increasing the force of the blades on the skin. This could not be achieved by prior art razors.

In addition, the handle can be arranged so as not to obstruct flow of rinsing water through the blade unit and in accordance with a preferred feature, with the blade unit in the rest position, the handle is located entirely forwardly of a plane containing the edge of the blade adjacent the guard and perpendicular to said plane containing said edge and the guard surface. (For convenience the latter plane is herein-after referred to as the "top plane" of the blade unit.) Ideally the handle is located entirely forwardly of a plane containing the trailing edge of the guard surface and perpendicular to the top plane of the blade unit.

The blade unit may be pivotally movable through an angle in the range of 35° to 50°, preferably 40° to 45°, from the rest position to a limit position, and both these end positions are conveniently defined by stops provided on the blade unit for abutment by the handle connection places.

In a specific embodiment of the invention, when the blade unit is in the rest position, the top plane thereof is at 20°-30° to the longitudinal axis of the handle, i.e. the axis of that part of the handle intended to be held in the hand. Furthermore, the pivot axis is 1.0-2.0 mm, preferably 1.25-1.75 mm, from the leading blade edge and 0.50-1.00 mm below the guard surface.

In accordance with a second aspect the invention provides a razor comprising a blade unit, and a handle mounting the

2

blade for pivotal movement, from a rest position, the handle being connected to the blade unit by a pair of opposed connection pieces engaging the blade unit at the respective ends thereof, characterised in that the connecting pieces are urged resiliently into abutment with cam faces on the blade unit whereby to oppose displacement of the blade unit from the rest position and to apply a restoring force for returning the blade unit to the rest position after having been pivoted away therefrom.

Conveniently the handle has a pair of wings with tips forming the connection pieces and biased apart by the wings. In one embodiment, the handle is intended to be used with blade units in the form of replaceable cartridges, and the wings are hinged elements acted upon by spring means incorporated in the handle structure. In another embodiment the wings are integral with the handle and are themselves resilient. In both cases the wing tips comprise pivot elements, particularly pins or stub axles, which cooperate with complementary means on the blade unit to define the pivotal connection between the handle and blade unit. Adjacent their pivot elements, the wing tips have edge surfaces which abut the cam faces. It will be appreciated that by virtue of the wing tips a simple pivot assembly with return spring is obtained. Furthermore, the blade unit can be made easily detachable by squeezing the wings together.

A full understanding of the invention will be gained from the following detailed description of some specific embodiments which are given by way of non-limiting example only, reference being made to the accompanying drawings in which:

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of a razor head portion, the blade unit thereof being shown in transverse cross section;
FIG. 2 is a section taken along the line A—A in FIG. 1;
FIG. 3 is a partial view of the underside of the blade unit;
FIG. 4 is section taken along the line B—B of FIG. 3; and
FIG. 5 is an exploded perspective view of an alternative embodiment.

DETAILED DESCRIPTION OF THE INVENTION

The safety razor illustrated in FIGS. 1 and 2 has a handle 1 and a blade unit or cartridge 2, the razor being of the type in which the cartridge is intended to be discarded when the blades have become dulled and to be replaced on the handle by a new cartridge with sharp blades. The blade cartridge includes a housing or frame 4 in which are received at least one blade, there being three blades 6 in the specific example shown, and a lubricating strip 8 which forms the cap of the assembly. The frame includes an integral guard member defining a guard surface 10 extending along the cartridge parallel to the leading blade edge 12. Of course, the guard surface could be defined instead by a separate member carried by the cartridge frame. At the opposite ends of the frame and adjacent the front edge thereof there are defined respective sockets 14 for reception of handle connection pieces. Each socket includes a longitudinally inwardly directed cam face 16. As best seen from FIG. 3, the cam faces are inclined to converge towards each other in the direction towards the rear of the cartridge. Immediately above each cam race is an aperture 18 directed longitudinally outwardly from the socket and having a centre which defines the pivot axis C of the cartridge when mounted on the handle.

5,794,354

3

The razor handle includes a main part, only partially shown intended to be grasped in the hand, and a neck in the form of a yoke with opposed arms having grooves or slots in which respective wings 20 are mounted by pivots 22. The free ends or tips of the wings are biased apart by leaf springs 24 incorporated in the handle and acting on the respective wings. As shown the wings include finger grip portions 25 intermediate their ends for squeezing the wings together against the action of the springs. The wing tips engage in the respective sockets 14 of the cartridge and have stub axles 26 which engage in the apertures 18 to form the pivot between the handle and blade unit and hence define the pivot axis C. The springs 24 acting on the wings urge the stub axles 26 into correct engagement in the apertures 18, but also press abutment edges 28 on the wing tips into contact with the cam faces 16. The sockets 14 have front and rear surfaces which serve as stops for the wing tips and thereby limit the pivotal movement of the cartridge with respect to the handle.

Due to the inclination of the cam faces 16, the wing tips bias the cartridge to a rest position, shown in FIG. 1, in which the wing tips engage the front stop surfaces 30 of the sockets 14. When the cartridge is pivotally displaced away from this position, e.g. during shaving, the cam faces 16 cam the wing tips inwardly towards each other and a gradually increasing restoring force tending to return the cartridge to the rest position is generated.

As may be seen clearly from FIG. 1, the axis C about which the cartridge pivots with respect to the handle underlies the guard surface 10, as seen in a direction perpendicular to the top plane P of the cartridge containing the guard surface and the leading blade edge 12. The displacement between the axis C and the leading blade edge, measured in the plane P, is substantially equal to 1.5 mm and the depth of the axis C below the surface 10 is substantially equal to 0.70 mm. In the rest position, the top plane P is at an angle substantially equal to 25° relative to the longitudinal axis of the main handle part. The rear faces 32 of the sockets 14 limit the maximum pivotal displacement of the cartridge to an angle of substantially 43°, as indicated in broken line in FIG. 1. When the cartridge is in the rest position, the rear of the cartridge is unencumbered by the handle, at least in the region of the blades, i.e. between the guard and cap. Blades 6 are mounted in opposed slots 100 at the sides of rinsing space 102. In particular, the handle is located entirely forwardly of a plane containing the trailing edge of the guard surface 10 and perpendicular to the top plane P.

To detach the cartridge, the handle wings 20 are squeezed together, e.g. between the thumb and forefinger. The stub axles 26 are retracted from the apertures 18 and the wing tip can then be withdrawn from the sockets 14. A fresh cartridge can then be mounted on the handle by the reverse procedure.

The embodiment shown in FIG. 5 is essentially the same as described above except that the wing tips with the stub axles and cam abutment edges are formed at the ends of integral wings 31 provided by a one-piece bifurcated handle. In this case the wings are resilient and their elasticity is relied upon to press the wing tips against the cam faces 16 of the cartridge.

I claim:

1. A safety razor comprising a blade unit (2) including a guard having a guard surface, at least one blade (6) having a blade edge, at least one additional blade, and a cap behind said additional blade, and a handle (1) mounting the blade unit for pivotal movement in one direction only from a rest position about a pivot axis, characterized in that the pivot axis (C) underlies the guard surface (10) as seen in a direction normal to a plane (P) containing the guard surface (10) and the blade edge (12) adjacent thereto, and a rinsing space open to the underside of the blade unit and defined

4

between the guard surface (10) and said cap and underlying said one blade and said additional blade, said rinsing space being substantially unobstructed by the handle to flow of rinsing water through said space when the blade unit is in the rest position.

2. A razor according to claim 1, wherein, when the blade unit is in the rest position, the handle is located entirely forwardly of a plane containing said blade edge of said at least one blade and perpendicular to said plane (P) containing the guard surface and said blade edge.

3. A razor according to claim 1, wherein, when the blade unit is in the rest position, the handle is located entirely forwardly of a plane containing the trailing edge of the guard surface (10) and perpendicular to said plane (P) containing the guard surface and said blade edge.

4. A razor according to claim 1, wherein the blade unit (2) is pivotable through an angle in the range of 35° to 50° preferably 40° to 45° from the rest position.

5. A razor according to claim 1 wherein, when the blade unit is in the rest position, said plane (P) containing the guard surface and said blade edge lies at an angle of 20° to 30° to the longitudinal axis of the handle.

6. A razor according to claim 1, wherein the pivot axis (C) is from 1.0 to 2.0 mm in front of said blade edge (12), measured in said plane (P) containing the guard surface and said blade edge.

7. A razor according to claim 1, wherein the pivot axis (C) is 0.50 to 1.00 mm below the guard surface.

8. A replaceable safety razor cartridge comprising a housing having a connecting structure for making a removable connection to a handle and a pivoting structure providing pivoting about a pivot axis,

a guard at the front of said housing,

a lubricating strip at the rear of said housing, and

first, second, and third blades carried by said housing between said guard and said lubricating strip,

whereby a user's beard is engaged sequentially by said guard, said first blade, said second blade, said third blade, and said lubricating strip during a shaving stroke,

wherein said pivot axis is in front of said blades and below a plane that is tangent to said guard and said lubricating strip,

said housing having a substantially unobstructed opening through it underneath said plane that is tangent to said guard and said lubricating strip, and wherein said first, second, and third blades are mounted in said opening.

9. The cartridge of claim 8 wherein each of said blades is disposed in a respective plane that is oriented at an acute blade angle to said plane that is tangent to said guard and said lubricating strip, and wherein said blades do not overlap each other.

10. The cartridge of claim 9 wherein said blades are mounted for movement with respect to said plane that is tangent to said guard and lubricating strip.

11. The cartridge of claim 8 wherein each of said blades is mounted on a bent support, each said bent support having a support portion and a base portion, said support portion being oriented at an acute blade angle with respect to said plane that is tangent to said guard and said lubricating strip, said base portion being generally perpendicular to said plane that is tangent to said guard and said lubricating strip.

12. The cartridge of claim 11 wherein each of said base portions is mounted in respective opposed slots in said housing on opposite sides of said opening.

13. The cartridge of claim 12 wherein said base portions are movable within said opposed slots.

* * * * *